


Pneumatic Drive Bellows Pump






Iwaki America's FS is a compact, all-temperature rated, low-cost, air-driven, bellows pump series designed for the semiconductor industry, chemical delivery or recirculation. This pump handles high temperature nitride etch and piranha etch applications with ease. FS features intelligent drive technology and leak sensing, with a significant cost savings over previous models, and a 2-year warranty.

Iwaki America's FS is rated for liquid temperatures ranging from 5° to 180°C with discharge pressures up to 73 psi, making it the perfect pump for wet process tools, cleaning and chemical feed applications. Utilizing stroke rates up to 240 spm, FS is able to produce up to 50% higher flow rates in a significantly smaller space. FS has a contamination-free design; all liquid contact parts are made of PTFE/PFA. The anti-torsion air chamber design eliminates the need for retorquing connecting rods. The intelligent sensor drive system of Iwaki America's FS design uses proximity switches and an external solenoid valve allowing the pump operation to be easily controlled and monitored.

Model	FS-15HT1/T2			FS-30HT1/T2			FS-60HT1/T2								
Max discharge capacity	4.0 GPM (15 LPM)			8.0 GPM (30 LPM)			14.5 GPM (55 LPM)								
Max air supply pressure MPa (PSI)	0.15-0.5 (22.5-75)	0.15-0.3 (22.5-45)	0.15-0.2 (22.5-30)	0.15-0.5 (22.5-75)	0.15-0.3 (22.5-45)	0.15-0.2 (22.5-30)	0.15-0.5 (22.5-75)	0.15-0.3 (22.5-45)	0.15-0.2 (22.5-30)						
Liquid temperature range °C (°F)	5-50 (41-122)	51-100 (123-212)	101-180 (213-356)	5-50 (41-122)	51-100 (123-212)	101-180 (213-356)	5-50 (41-122)	51-100 (123-212)	101-180 (213-356)						
Max air consumption NL/min	200	160	110	200	160	110	200	160	110						
Max stroke speed SPM	240			220			200								
Pump connection size PFA	1/2", OD 0.5" x ID 0.385"			3/4", OD 0.75" x ID 0.63"			1", OD 0.98" x ID 0.87"								
Air supply connection size	PT 1/4, Rc 1/4			PT 1/4, Rc 1/4			PT 3/8, Rc 3/8								
Ambient temperature	32-104°F (0-40°C)														
Drive system	by proximity switch or APT valve														
Self-priming ability	3.3 FT (1.0 m)			6.6 FT (2.0 m)			6.5 FT (2.0 m)								
Wetted materials	PTFE, PFA														



Performance Curves



IALT-00038.D Aug 2012

www.IwakiAmerica.com

Five Boynton Road • Holliston, MA • 01746 USA • Tel: 508-429-1440 • Fax: 508-429-1386 info@iwakiamerica.com

